



PROTECTOR FG ALUMINIUM COMPLEX R2 V150

Description

PROTECTOR FG ALUMINIUM COMPLEX is a grease developed for use in the food processing industry, in all applications that require greases with excellent performance at high working temperatures. Formulated using an Aluminium Complex thickener, this grease has a strong affinity for metal and it is highly stable when operating with heavy loads and at high temperatures. Thanks to its fully synthetic base oil, this grease can work continuously at temperatures close to 180°C. The carefully balanced additives, improved with solid PTFE content, yield excellent anti-corrosive, anti-oxidant, anti-wear, and extreme pressure-resistant properties, all of which are needed to guarantee the proper performance in the most demanding applications.

This grease has excellent sealing properties, ideal for lubricating bearings subjected to high temperatures and pressures. It is registered as an H1 category grease.

Properties

- Wide range of working temperatures (-40/180°C).
- Long-lasting lubrication thanks to its solid PTFE content.
- Great adhesive and lubricating properties.
- Fully compatible with gaskets and conventional paints.
- Registered as an H1 lubricant with the NSF.
- MOAHs free (Mineral Oil Aromatic Hydrocarbon).

Main applications

- Bearings that operate at extreme temperatures, capable of supporting heavy loads.
- Bearings in refrigeration facilities, owing to its good fluidity at low temperatures.
- Bearings that require a lubricant with excellent adhesive and sealing properties.

Quality levels, approvals and recommendations

• NSF: H1*

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Colour		Visual	Ivory
NSF registration number H1			157624
Type of thickener			Complejo de Aluminio
Base oil			Synthetic
Consistency	NLGI		2
Penetration, 25 °C, 60 strikes worked	1/10 mm	ASTM D217	280
EP properties 4B,weld point	kg	IP 239	>400
Dropping point	°C	ASTM D566	240
Fluidity pressure at -35°C		DIN 51805	<1000
Emcor corrosion test		DIN 51802	<0,5

The above mentioned characteristics are typical values and should not be considered product specifications.

