



## MAKER DESMOLDOIL PU

### Description

Products from the DESMOLDOIL range are compounds formulated to act as mould-release agents in various applications. They are made up of a selected blend of base stocks.

The range of DESMOLDOIL products has been carefully designed to guarantee compliance with our customers demands in relation to all kinds of applications and finishes (pieces of concrete, formwork, etc.) on any kind of surface, such as wood, iron, etc.

### Properties

- Good oxidation resistance and storage stability.
- Excellent mould release properties.
- Outstanding surface coverage.
- Excellent finishing.

### Technical specifications

|                       | UNIT              | METHOD     | VALUE |
|-----------------------|-------------------|------------|-------|
| Colour                |                   | ASTM D1500 | L 0,5 |
| Density at 15 °C      | g/cm <sup>3</sup> | ASTM D4052 | 0.832 |
| Viscosity at 40 °C    | cSt               | ASTM D445  | 8.78  |
| Viscosity at 100 °C   | cSt               | ASTM D445  | 2.43  |
| Viscosity index       | -                 | ASTM D2270 | 93    |
| Flash point, open cup | °C                | ASTM D92   | 176   |
| Pour point            | °C                | ASTM D97   | -48   |

The above mentioned characteristics are typical values and should not be considered product specifications.