



RACING SYNTH 2T

Description

100% synthetic lubricant oil and with ester for 2-stroke engines. Suitable for competition and for daily use. Lubricant oil formulated with ester to provide total engine protection and immediate acceleration. Moreover, it is especially suitable for low contaminating emission engines; its composition prevents the formation of deposits in the exhaust system, which prolongs its life and engine life. It is suitable for engines with a premix in the fuel and also for those that use an injector lubrication system.

Properties

- Formulated to provide total protection, excellent for ensuring a clean engine and low emissions.
- Its components prevent the formation of deposits, helping to keep the exhaust ports clean.
- It extends the engine's lifespan, preventing any sticking of the piston rings, sweating of spark plugs and the formation of carbonous residues.
- It minimises the emission of fumes, contributing to a reduction in pollution.

Quality levels, approvals and recommendations

- API: TC
- ISO: L-EGB
- TISI: 1040

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm ³	ASTM D4052	0.869
Kinematic viscosity at 100 °C	cSt	ASTM D445	10
Kinematic viscosity at 40 °C	cSt	ASTM D445	56
Viscosity index	-	ASTM D2270	144
Flash point, open cup	°C	ASTM D92	165
Pour point	°C	ASTM D97	-24
TBN	mg KOH/g	ASTM D2896	1.8
Sulphated ashes	% in weight	ASTM D874	0.19

The above mentioned characteristics are typical values and should not be considered product specifications.