

SMARTER SCOOTER 2T

MOTO

Description

It is the ideal synthetic lubricant oil for 2-stroke engine scooters since it has been designed for continual stop-start use, which is so typical of this type of motorcycle. It provides excellent protection against wear and it minimises the emission of contaminating fumes. Furthermore, it supports high engine temperatures in an exemplary way and prevents the formation of carbon deposit in the pistons and the degradation of the exhaust systems. It is suitable for both premix and injector lubrication engines.

Properties

- Reduces exhaust emissions due to its “smokeless” technology.
- Minimises engine noise.
- Good thermal stability and antioxidant capacity.
- Increases the smoothness and power of the engine.
- Increased protection against wear.

Quality levels, approvals and recommendations

- JASO M345 FD*
 - API TC
 - Aprilia DFI
 - ISO-L-EGD
 - TISI
- *Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm ³	ASTM D 4052	0,870
Viscosity at 100 °C	cSt	ASTM D 445	9,6
Viscosity at 40 °C	cSt	ASTM D 445	64
Viscosity index	-	ASTM D 2270	130
Flash point, open cup	°C	ASTM D 92	115
Pour point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	2
Sulphated ashes	% weight	ASTM D 874	0,1

The above mentioned characteristics are typical values and should not be considered product specifications.