



Description

Multigrade lubricant oil suitable for the engines of light petrol vehicles that only require API SL quality level. It provides great resistance to oxidation, increasing the time between oil changes. The oil's viscosity facilitates engine start-up.

Properties

- Keeps the engine clean, reducing deposit formation and increasing service life.
- Contains anti-wear additives that minimise wear on the engine's parts.
- Suitable for vehicles that use CNG or LPG as fuel.

Quality levels, approvals and recommendations

- API SL

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W-40
Density at 15 °C	g/cm ³	ASTM D4052	0.871
Kinematic viscosity at 40 °C	cSt	ASTM D445	91
Kinematic viscosity at 100 °C	cSt	ASTM D445	13.5
CCS Viscosity at -25 °C	cP	ASTM D5293	< 7.000
HTHS, viscosity at 150 °C	cP	ASTM D5481	> 3.5
Viscosity index	-	ASTM D2270	> 140
Flash point, open cup	°C	ASTM D92	> 215
Pour point	°C	ASTM D97	-40
Noack volatility, 1h at 250 °C	% in weight	CEC L-40-93	< 15
Shearing Inj.Bosch: Vis 100 °C (30 cy)	cSt	CEC L-14-93	> 11.5
TBN	mg KOH/g	ASTM D2896	6

The above mentioned characteristics are typical values and should not be considered product specifications.