



Description

Multigrade lubricant oil designed for use in light petrol vehicles. Recommended for petrol engines that require API SL quality level.

Properties

- Multigrade oil that keeps the engine clean.
- Its formulation minimises the formation of deposits and sludge.
- Protects the engine's metal parts against corrosion.
- Suitable for vehicles that use CNG or LPG as fuel.

Quality levels, approvals and recommendations

- API SL

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			15W-40
Density at 15 °C	g/cm ³	ASTM D4052	0.868
Kinematic viscosity at 40 °C	cSt	ASTM D445	100
Kinematic viscosity at 100 °C	cSt	ASTM D445	14
CCS Viscosity at -20 °C	cP	ASTM D5293	< 7.000
HTHS, viscosity at 150 °C	cP	ASTM D5481	> 3.7
Viscosity index	-	ASTM D2270	143
Flash point, open cup	°C	ASTM D92	> 215
Pour point	°C	ASTM D97	-39
Noack volatility, 1h at 250 °C	% in weight	CEC L-40-93	< 15
Shearing Inj.Bosch: Vis 100 °C (30 cy)	cSt	CEC L-14-93	> 12.5
TBN	mg KOH/g	ASTM D2896	6

The above mentioned characteristics are typical values and should not be considered product specifications.