



Description

Multigrade lubricant oil designed for use in light petrol vehicles. Recommended for petrol engines that require API SL quality level and greater protection at high temperatures.

Properties

- Multigrade oil that keeps the engine clean.
- Its high viscosity helps to seal the engine and prevent leaks.
- Its formulation minimises the formation of deposits. Great anti-wear properties that protect even the most sensitive parts of the engine.
- Suitable for vehicles that use CNG or LPG as fuel.

Quality levels, approvals and recommendations

- API SL

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			20W-50
Density at 15 °C	g/cm3	ASTM D4052	0.884
Kinematic viscosity at 40 °C	cSt	ASTM D445	161
Kinematic viscosity at 100 °C	cSt	ASTM D445	18.5
CCS Viscosity at -15 °C	cP	ASTM D5293	› 9.500
HTHS, viscosity at 150 °C	cP	ASTM D5481	› 3.7
Viscosity index	-	ASTM D2270	129
Flash point, open cup	°C	ASTM D92	› 215
Pour point	°C	ASTM D97	-39
Noack volatility, 1h at 250 °C	% in weight	CEC L-40-93	‹ 15
Shearing Inj.Bosch: Vis 100 °C (30 cy)	cSt	CEC L-14-93	› 16.3
TBN	mg KOH/g	ASTM D2896	7.3

The above mentioned characteristics are typical values and should not be considered product specifications.