



## Description

ACEA C4 quality synthetic lubricant oil, specially recommended in vehicles with particle filters and exhaust fume treatment. It stands out for its low ash formation (Low SAPS), and it is most adequate for Renault diesel vehicles that require RN0720 quality level. It is also a long-lasting lubricant, allowing significant extension of oil change intervals; always according to the manufacturer's recommendations. Its performance levels mean that it can be used in vehicles that require ACEA C3 or ACEA C4.

## Properties

- Its reduced ash content (Low SAPS) makes it essential for ensuring the durability of new technologies applied to reduce pollutant emission levels, such as diesel particle filters (DPF).
- The RN0720 quality level ensures high oil resistance to oxidation and a minimum formation of deposits in the piston, thus extending the oil change period.
- Contributes to reducing CO2 emissions, obtaining fuel savings of up to 1 % compared to other lubricants under standard M111FE test conditions.

## Quality levels, approvals and recommendations

- ACEA C4
- FIAT Meets FIAT 9.55535 S4
- MB 226.51
- RENAULT RN0720

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			5W-30
Density at 15 °C	g/cm3	ASTM D4052	0.850
Kinematic viscosity at 40 °C	cSt	ASTM D445	71
Kinematic viscosity at 100 °C	cSt	ASTM D445	12.2
CCS Viscosity at -30 °C	cP	ASTM D5293	<6,600
Viscosity index	-	ASTM D2270	168
Flash point, open cup	°C	ASTM D92	>200
Pour point	°C	ASTM D97	-45
TBN	mg KOH/g	ASTM D2896	8.2

The above mentioned characteristics are typical values and should not be considered product specifications.