



Description

High-performance mineral oil designed for a wide variety of two-stroke engines. This oil can be used to lubricate anything from small two-stroke gardening engines to chainsaw engines and small forestry industry vehicles, thanks to the use of our highly-refined mineral bases and combination of additives. It is a clean oil which takes care of the engine, protecting all metallic pieces from wear and corrosion and offering optimal lubrication for the combustion chamber.

Properties

- High lubricating power, reducing wear and extending the engines life.
- Minimizes the formation of deposits, keeping exhaust ports clean.
- Reduces spark plug fouling and prevents piston rings from sticking.

Quality levels, approvals and recommendations

• API TC

• ISO L-EGB

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm3	ASTM D4052	0.882
Kinematic viscosity at 40 °C	cSt	ASTM D445	65
Kinematic viscosity at 100 °C	cSt	ASTM D445	8.9
Viscosity index	-	ASTM D2270	110
Flash point, open cup	°C	ASTM D92	146
Pour point	°C	ASTM D97	-15
Sulphated ashes	% in weight	ASTM D874	0.1
TBN	mg KOH/g	ASTM D2896	1.6

The above mentioned characteristics are typical values and should not be considered product specifications.