



Description

High quality monograde mineral lubricant oil formulated from a very refined base; it contains specially selected additives which enhance characteristics such as resistance to oxidation, anti-wear power and detergency-dispersancy, among others. This prolongs its useful life.

It may be used as a hydraulic fluid in public works machinery, and in transmissions in which the manufacturer recommends this degree of viscosity.

Properties

- Significant detergent-dispersant power, which prevents the formation of deposits.
- Very good anticorrosion and antirust properties, which ensures greater protection of the metallic elements.
- Low pour point.
- Excellent antifoam properties.
- Excellent performance with regard to joints and elastomers, which ensures greater compatibility with the different parts of the hydraulic system.

Quality levels, approvals and recommendations

- ALLISON C-3
- API CF/SF
- CATERPILLAR CAT TO-2

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W
Density at 15 °C	g/cm3	ASTM D4052	0.880
Kinematic viscosity at 40 °C	cSt	ASTM D445	39
Kinematic viscosity at 100 °C	cSt	ASTM D445	6.6
Viscosity index	-	ASTM D2270	110
Flash point, open cup	°C	ASTM D92	>200
Pour point	°C	ASTM D97	-27
Sulphated ashes	% in weight	ASTM D874	1.3
TBN	mg KOH/g	ASTM D2896	8.9

The above mentioned characteristics are typical values and should not be considered product specifications.