



MAKER SUPER TAURO PAG

Description

High-performance lubricants, 100% synthetic (polyglycols). They have latest-generation additives which make them specially suitable for applications under severe conditions within a wide temperature range: from -30 to over 200 °C. They are specially developed to provide extra protection against corrosion and water separation. Maker Super Tauro PAG oils have superior performance characteristics to conventional gear oils and are suitable for systems requiring high levels of resistance to oxidation and load capacity.

Properties

- Exceptional resistance to oxidation at high temperatures
- Low pour point, allowing operation at low temperatures
- Very high viscosity index, allowing lubrication within a wide range of temperatures
- Exceptional friction coefficient, which makes them specially recommendable for worm drive dividers
- Free of chlorine and sulphur or lead-based compounds
- Minimum formation of deposits
- Excellent water separation and anti-foam properties
- Very good anti-rust and anti-corrosion protection
- Optimum EP properties
- Compatible with most joints and retainers

Quality levels, approvals and recommendations

- AGMA 9005-F16 (antigua 9005-E02-EP)
 - AIST 224 (US Steel 224)
 - DANIELI STANDARD N. 0.000.001 - REV.15*
 - DIN 51517/3 - CLP
 - ISO 6743/6 CKT
 - NEGRI BOSSI ELEOS, eCANBIO JANUS Y VESTA series (220)*
 - WEG-CESTARI WCG20 (220)*
 - WEG-CESTARI WCG50 (320)*
 - ZANINI RENK 00-90263/4n*
- *Formal approval



MAKER SUPER TAURO PAG

Technical specifications

	UNIT	METHOD	VALUE	
ISO Viscosity Grade			220	320
Density at 15 °C	g/cm3	ASTM D4052	1,006	1,005
Kinematic viscosity at 40 °C	cSt	ASTM D445	220	320
Kinematic viscosity at 100 °C	cSt	ASTM D445	32	45
Viscosity index	-	ASTM D2270	180	195
4 Ball EP, welding load	kg	ASTM D2783	175	170
Flash point, open cup	°C	ASTM D92	290	295
FZG (A/8,3/90): Failure load stage	-	ISO 14635	>12	>12
Pour point	°C	ASTM D97	-33	-36
Rust, Methods A and B	-	ASTM D665	Pass	Pass
Water separability at 82 °C	min	ASTM D1401	30	30

The above mentioned characteristics are typical values and should not be considered product specifications.