



MAKER SUPER TAURO

Description

The Maker Super Tauro range of oils has been developed for applications in industrial gear assemblies with high load requirements. Its careful formulation incorporates the highest quality bases and additives, improving its anti-rust properties, its anti-foaming capacity and its resistance to oxidation. As such, these oils offer an excellent performance that puts them ahead of their competition.

They are particularly suitable for all kinds of industrial reducers and multipliers, using splash or circulating lubrication. Very effective in all cases requiring maximum levels of oxidation resistance and/or load capacity.

Properties

- Reduce wear under boundary lubrication conditions and extreme pressure
- Excellent thermal stability
- Very good protection against rust, preventing steel corrosion
- High de-emulsifying capacity (quick separation from water)
- Good antifoaming characteristics
- Resistance to the rupture of the lubricant film

Quality levels, approvals and recommendations

- AGMA 9005-F16 (antigua 9005-E02-EP)
- AIST 224 (US Steel 224)
- BALIÑO BALIÑO: 0071GE-ES para la hélice de maniobra (68)
- BALIÑO BALIÑO: 0074GE-ES para bocina (100)
- BATTENFELD Inyectoras (68)
- DANIELI STANDARD N. 0.000.001 - REV.15 (150, 220, 320, 460, 680)*
- DAVID BROWN S1.53.101
- DIN 51517/3 - CLP
- ENGEL Engel Injection Moulding Machines (320)*
- FIVES CINCINNATI P-34 (680)
- FIVES CINCINNATI P-35 (460)
- FIVES CINCINNATI P-59 (320)
- FIVES CINCINNATI P-63 (68)
- FIVES CINCINNATI P-74 (220)
- FIVES CINCINNATI P-76 (100)
- FIVES CINCINNATI P-77 (150)
- FIVES CINCINNATI P-78 (1000)
- IBERCISA Rodamientos (220, 320)*
- ISO 12925-1 CKD
- LEMASA High Pressure Pumps (220)*
- MANULI Gear (320)*
- NEGRI BOSSI ELEOS, eCANBIO JANUS Y VESTA series (320, 68)*
- REINTJES BV1597/2, BV2060/2 (100)*
- REINTJES BV1597/4, BV2060/4 (150)*
- SCHOTTEL GOST 23652-79 TAP-15V (100, 150, 220, 68)*
- WEG-CESTARI WCG20 (220)*
- WEG-CESTARI WCG50 (320)*

*Formal approval



MAKER SUPER TAURO

Technical specifications

	UNIT	METHOD	VALUE							
ISO Viscosity Grade			68	100	150	220	320	460	680	1000
Density at 15 °C	g/cm3	ASTM D4052	-	0.889	0.893	0.897	0.901	0.904	-	0.903
Kinematic viscosity at 40 °C	cSt	ASTM D445	68	100	150	220	320	460	680	1000
Kinematic viscosity at 100 °C	cSt	ASTM D445	8.5	11	14.5	19	23	30	40	50
Viscosity index	-	ASTM D2270	98	97	97	95	93	92	95	95
Corrosion Cu, 3hrs 100 °C	-	ASTM D130	1b	1b	1b	1b	1b	1b	1b	1b
Flash point, open cup	°C	ASTM D92	230	245	260	260	260	260	260	260
FZG (A/8,3/90): Failure load stage	-	ISO 14635	>12	>12	>12	>12	>12	>12	>12	>12
Pour point	°C	ASTM D97	-12	-12	-9	-9	-9	-9	-9	-6
Rust, Methods A and B	-	ASTM D665	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
TAN	mg KOH/g	ASTM D664	0,20	0,20	0,20	0,20	0,20	0,20	0,20	0,20
Timkem load	lb	ASTM D2782	>60	>60	>60	>60	>60	>60	>60	>60
Water separability at 54 °C	min	ASTM D1401	<30	-	-	-	-	-	-	-
Water separability at 82 °C	min	ASTM D1401	-	<30	<30	<30	<30	<30	<60	<60

The above mentioned characteristics are typical values and should not be considered product specifications.

Safety data sheets are available at: <https://lubricants.repsol.com/en/>

Lubricant Technical File RP_6128I, RP_6128J, RP_6128L, RP_6128M, RP_6128N, RP_6128Q, RP_6128R, RP_6128S

April 2025