



Description

Extreme Pressure multigrade lubricant oil recommended for use in vehicle differentials or hypoid and helical transmissions, as well as transmission final drives for trains and manual gearboxes requiring API GL-5 oil.

Properties

- Excellent capacity for withstanding peak loads and temperatures. Extreme Pressure (EP).
- Very good resistance to ageing.
- Excellent antirust and antifoam properties.
- Aids lubrication at low temperatures.
- As it is a multigrade oil it offers excellent protection in very severe temperature and use conditions.
- Offers a better response to manual gearbox synchronisation than a monograde oil thanks to its lower friction in gear cogs, particularly at low temperatures.
- Good antiwear properties, thus extending useful transmission life.

Quality levels, approvals and recommendations

- API GL-5
- MIL L-2105D
- VOLVO 97310
- ZF TE-ML 05A, 07A, 08, 12E, 16C, 16D, 21A

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			85W-140
Density at 15 °C	g/cm3	ASTM D4052	0.914
Kinematic viscosity at 40 °C	cSt	ASTM D445	400
Kinematic viscosity at 100 °C	cSt	ASTM D445	28.3
Brookfield Viscosity at -12 °C	cP	ASTM D2983	<150,000
Viscosity index	-	ASTM D2270	>95
Flash point, open cup	°C	ASTM D92	>190
Pour point	°C	ASTM D97	-18
FZG (A/8,3/90): Failure load stage	-	ISO 14635	>12
4 Ball EP, wear load index	-	ASTM D2783	>50

The above mentioned characteristics are typical values and should not be considered product specifications.