



Description

Synthetic brake fluid designed for hydraulic systems in motorcycles that operate in severe conditions where the recommended quality level is DOT 4 or DOT 3. Guarantees maximum efficiency and the highest stability in the functioning of the break pump.

Properties

- High boiling point: above 260 °C
- Prevents foam formation.
- Highly resistant to oxidation.
- Compatible with joints and seals, thus preventing fluid loss risks.
- Contains inhibitors that prevent corrosion of the metal components of the circuit.

Quality levels, approvals and recommendations

- SAE J 1703/J 1704
- FMVSS 116 DOT 4
- ISO 4925
- INTA Approved by the official INTA laboratory according to UNE 26-109-88
- JIS K2234:2018

Technical specifications

	UNIT	METHOD	VALUE
Water content	ppm	ASTM D6304	<2,000
pH value	-	SAE J1704	9
Appearance	-	Visual	Yellowish liquid
Density at 20 °C	g/cm3	DIN 51757-4	1.04
Kinematic viscosity at 100 °C	cSt	ASTM D445	>1.5
Viscosity at -40 °C	cP	SAE J1704	<1,500
Reflux boiling point	°C	SAE J1704	260
Wet boiling point	°C	SAE J1704	160

The above mentioned characteristics are typical values and should not be considered product specifications.