



Description

Lubricant oil formulated for lubricating motorcycle gearboxes. It provides excellent resistance to shearing and ensures that oil bath clutches operate with perfect slipping control in extreme conditions. It prolongs the life of all gearbox components, reduces mechanical noise and helps cold starts..

Properties

- Maximum protection against wear and extreme conditions for all parts of the gearbox.
- Provides optimum friction in clutch discs, preventing slippage.
- Enables speed and clutch changes to be carried out smoothly and precisely.

Quality levels, approvals and recommendations

• API SN

• JASO T 903:2016 MA2*

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm3	ASTM D4052	0.851
Kinematic viscosity at 40 °C	cSt	ASTM D445	89
Kinematic viscosity at 100 °C	cSt	ASTM D445	14.1
CCS Viscosity at -25 °C	cP	ASTM D5293	<7,000
Viscosity index	-	ASTM D2270	160
Flash point, open cup	°C	ASTM D92	244
Pour point	°C	ASTM D97	-33
Sulphated ashes	% in weight	ASTM D874	0.8
TBN	mg KOH/g	ASTM D2896	7

The above mentioned characteristics are typical values and should not be considered product specifications.