



## QUALIFIER TRANSMISSION 75W

### Description

Synthetic oil for transmissions of motorcycles. It improves substantially the quickness and precision of the gearshift, enhancing at the same time the smoothness and progressivity of the clutch. This lubricant is specially recommended in severe driving conditions.

### Properties

It has excellent oxidation stability, even in extreme high temperature conditions, thus making the product more durable, which enables long drainage periods

Its excellent fluidity at low temperature enables speed and clutch changes to be carried out smoothly and precisely

Maximum protection against wear for all parts of the gearbox, which enhances the durability of the mechanisms.

Proof of performance in trial motorcycles

It is also valid for use in the gearbox of passenger cars or light duty models when this viscosity is required

### Quality levels, approvals and recommendations

• API GL-4, GL-5

### Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm3	ASTM D4052	0.841
Kinematic viscosity at 40 °C	cSt	ASTM D445	25
Kinematic viscosity at 100 °C	cSt	ASTM D445	5.1
Viscosity index	-	ASTM D2270	140
Brookfield Viscosity at -40 °C	cP	ASTM D2983	4,000
Flash point, open cup	°C	ASTM D92	200
Pour point	°C	ASTM D97	-72
TBN	mg KOH/g	ASTM D2896	4.5

The above mentioned characteristics are typical values and should not be considered product specifications.