



Description

Semi-synthetic oil essentially suitable for high performance small cylinder capacity 2-stroke engines. Its formulation protects the engine against the formation of deposits in the exhaust and the degradation of engine components. It is suitable for both premix and for injector lubrication system engines. It is perfectly suitable for all types of 2-stroke motorcycles in their very varied disciplines.

Properties

- Highly stable lubricant film.
- Reduces friction and wear.
- Good thermal and oxidative stability.
- Prevents the spark plugs sweating, the pistons from sticking, and the formation of carbonous residues.

Quality levels, approvals and recommendations

- API TC
- APRILIA DFI
- ISO L-EGD
- JASO M345 FD*
- TISI 1040
- *Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm3	ASTM D4052	0.870
Kinematic viscosity at 40 °C	cSt	ASTM D445	68
Kinematic viscosity at 100 °C	cSt	ASTM D445	10.0
Viscosity index	-	ASTM D2270	130
Flash point, open cup	°C	ASTM D92	116
Pour point	°C	ASTM D97	-33
Sulphated ashes	% in weight	ASTM D874	0.1
TBN	mg KOH/g	ASTM D2896	2

The above mentioned characteristics are typical values and should not be considered product specifications.