



## Description



Marine lubricant with a patented formula specially designed for the lubrication of cylinders of 2-stroke low-speed diesel engines that run on a wide range of fuels with a sulphur content from 0% to 1.5%.

The unique composition of TALUSIA UNIVERSAL endows it with exceptional capacity to neutralise acids during combustion.

Designed for the most severe working conditions, TALUSIA UNIVERSAL is suitable for special working conditions using fuels with a sulphur content of between 0.5% and 3.5%.

TALUSIA UNIVERSAL is a premium solution for the lubrication of all modern diesel and dual-fuel two-stroke engines using IMO 2020 and ECA compliant fuels.

## Properties

- Minimum wear of the piston liner and rings with maximum cleanliness.
- Reduces engine maintenance costs, extending the time between revisions.

## Quality levels, approvals and recommendations

- EVERLLENCE (MAN B&W)\*
- JAPAN ENGINE CORPORATION (UE ENGINES)\*
- WinGD (Wärtsilä)\*
- WinGD WinGD DF Validated\*

\*Formal approval

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			50
Density at 15 °C	g/cm3	ASTM D4052	0.930
Kinematic viscosity at 100 °C	cSt	ASTM D445	19
Flash point, open cup	°C	ASTM D92	≥230
Pour point	°C	ASTM D97	-9
TBN	mg KOH/g	ASTM D2896	57

The above mentioned characteristics are typical values and should not be considered product specifications.