



AUTOMATOR ATF VI

Description

AUTOMATOR ATF VI is a low viscosity and fully synthetic lubricant approved by General Motors for use in all their automatic transmissions, exceeding Dexron III, Dexron II and TASA. Recommended for light vehicles, commercial vehicles and some heavy duty.

Properties

- Low viscosity fluid for maximum fuel economy compared with fluids that meet DEXRON III.
- Improves performance and service life compared to previous automatic transmission fluids (ATF), thus reducing maintenance.
- Compatible with joints and seals.
- Excellent oxidation resistance which reduces deposit formation and prolongs transmission life.
- Ensures smooth, silent gear change and efficient power transfer under all service conditions thanks to its friction modifiers.

Quality levels, approvals and recommendations

- DEXRON: VI*
- AISIN WARNER: JWS 3309 (T-IV) & JWS 3324 (WS), AW-1
- AUDI 5 HP LT71141
- BMW: JWS 3309 (T-IV), LA2634 y ETL-8072B
- BMW: M-1375.4
- CHRYSLER: MOPAR AS 68 RC (T-IV) y JWS 3309
- FIAT: T-IV type, JWS 3309
- FORD: MERCON LV
- HONDA: ATF-Z1 (except in CVTs) y DW-1
- HYUNDAI/KIA: SPH-IV
- ISUZU BESCO: ATF-II, ATF-III, ATF SP
- JAGUAR: ATF 3403, JLM20238
- JAGUAR: ATF LT71141, ZF 5HP24
- LAND ROVER: LR023288
- MAZDA: FZ
- MITSUBISHI: DIAQUEEN SK, SP-II y SP-III
- OPEL (all vehicles)
- PEUGEOT: ZF 4HP20
- PORSCHE: T-IV (JWS 3309)
- SAAB: 93 165 147
- SUBARU: ATF, ATF 5AT y ATF HP
- TOYOTA: ATF D-II, D-III, T-III, T-IV y WS
- VW: 5 HP (ZF 5 HP 30), 5 HP (18 FL, 30), 5 HP (19FL, 24A), G 052 162 (ZF Lifeguardfluid 5) y TL 521 62
- VW: G 055 162-A2, A6 (ZF LifeguardFluid 6 Plus)
- GM DEXRON VI*
- ALLISON: C-4
- BMW: 83 22 2 152 426
- BMW: LT 71141 (ZF 5 HP 18FL/19FL/24A)
- CHRYSLER: 68157995AA
- FIAT: 9.55550-AV5
- FORD: FNR5 (Mazda M5, XT-9-QMM5)
- FORD: WSS-M2C924-A
- HYUNDAI/KIA: NWS-9638
- HYUNDAI: SP-IV, SP-IV M (SP4-M), SP-IV-RR y SP-III
- JAGUAR: 02JDE26444
- JAGUAR: ATF 3403-M115
- JASO: M315 1A-LV
- MAZDA: ATF M-III y ATF M-V
- MITSUBISHI: ATF J3
- NISSAN: MATIC FLUID C, D, J, K, y S
- Peugeot/Citroen (PSA): AL4 Automatic gearbox oil (#9730.AE)
- PORSCHE: ATF 3403-M115
- PORSCHE: ZF 5HP19FL, ZF 5HP20, LT71141
- SAAB: T-IV (JWS 3309)
- SUZUKI: ATF 2326
- VOLVO: CE 97340
- VW: G 055 005 (ZF LifeguardFluid 6)
- VW: G 060 162- A2 (ZF lifeguardFluid 8)



AUTOMATOR ATF VI

• ZF TE-ML: 5L, 09, 11A, 11B, 21L

• ZF: 3, 4, 6, 8 and 9 speed transmissions

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE
Colour	-	Visual	Red
Density at 15 °C	g/cm ³	ASTM D4052	0.847
Kinematic viscosity at 100 °C	cSt	ASTM D445	6.0
Kinematic viscosity at 40 °C	cSt	ASTM D445	30
Brookfield Viscosity at -40 °C	cP	ASTM D2983	< 15.000
Viscosity index	-	ASTM D2270	151
Flash point, open cup	°C	ASTM D92	216
Pour point	°C	ASTM D97	-49

The above mentioned characteristics are typical values and should not be considered product specifications.