

## DRIVER HGX

### Description

Monograde lubricant oil particularly indicated for use in 4-stroke petrol and diesel engines that are not subject to demands beyond standard requirements and in some petrol engines with low performance and engine speeds. Made with refined mineral base oils and its additives control oxidation, effectively preventing the corrosion and wear of internal engine parts.

### Properties

- Oil with anti-wear properties.
- Good anti-corrosion properties.
- Low consumption and stable against oxidation thanks to the use of refined and low volatility base oils.

### Quality levels, approvals and recommendations

- API: SG/CF

### Technical specifications

	UNIT	METHOD	VALUE	VALUE
SAE Grade			40	50
Density at 15 °C	g/cm <sup>3</sup>	ASTM D4052	0.896	0.900
Kinematic viscosity at 100 °C	cSt	ASTM D445	14.9	19.3
Kinematic viscosity at 40 °C	cSt	ASTM D445	141	220
Viscosity index		ASTM D2270	> 95	> 95
Flash point, open cup	°C	ASTM D92	> 230	> 230
Pour point	°C	ASTM D97	-24	-24
TBN	mg KOH/g	ASTM D2896	9	9
Sulphated ashes	% in weight	ASTM D874	1.3	1.3

The above mentioned characteristics are typical values and should not be considered product specifications.