

**GUARD REFRIGERANTE ORGANICO 30 % / GUARD COOLANT OAT 30 %****Description**

Ethylene glycol-based engine coolant. With added fully organic inhibitors (OAT) that offer good protection against corrosion in all metals. Although it may be used in all types of cooling circuits (aluminium, copper, cast) it is particularly recommended in all high pressure aluminium engines where protection at high temperatures is very important.

**Properties**

- Product designed for direct consumption as it contains water treated to prevent hazards due to the formation of calcareous deposits and to prevent corrosion.
- Its thermal characteristics enable good engine cooling without the fluid boiling.
- Compatible with the metals and alloys present in cooling circuits: aluminium, copper, cast, brass and the most modern alloys.
- Environmentally friendly: does not contain nitrites, amines, phosphates (NAP free) nor silicates.
- Compatible with joints, seals and paints.

**Quality levels, approvals and recommendations**

- ASTM: D 3306
- BS: 6580
- UNE: 26-361-88

**Technical specifications**

	UNIT	METHOD	VALUE
Concentration			30%
Colour	-	Visual	Yellow
Active ingredient	% in weight	-	30
Density at 20 °C	g/cm <sup>3</sup>	ASTM D5931	1,042
Freezing point	°C	-	-18

The above mentioned characteristics are typical values and should not be considered product specifications.