

LEADER A3/B4 10W-40

Description

Semi-synthetic multigrade lubricating oil for use in engines of cars and light commercial vehicles. It combines high resistance to oxidation to optimise the change period, and a viscosity which facilitates vehicle starting, thus reducing wear.

Properties

- Multigrade lubricant with semi-synthetic base oils.; It can be used in the petrol and diesel engines of most vehicle manufacturers.
- Its outstanding features include resistance to the formation of deposits at high temperatures and of sludge at low temperatures, thus keeping the engine clean and increasing its durability.
- As a lubricant it is resistant to the loss of viscosity that occurs with some multigrade oils during their use. Thus the engine is kept properly lubricated during the entire period that the oil is used.

Quality levels, approvals and recommendations

- ACEA: A3/B4
- API: SN/CF
- MB: 229.1
- VW: 501 01/505 00

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W-40
Density at 15 °C	g/cm ³	ASTM D4052	0.857
Kinematic viscosity at 100 °C	cSt	ASTM D445	13.7
Kinematic viscosity at 40 °C	cSt	ASTM D445	90
CCS Viscosity at -25 °C	cP	ASTM D5293	<7,000
Viscosity index	-	ASTM D2270	156
Flash point, open cup	°C	ASTM D92	>215
Pour point	°C	ASTM D97	-39
TBN	mg KOH/g	ASTM D2896	10.7
Shearing Inj.Bosch: Vis 100 °C (30 cy)	cSt	CEC L-14-93	>12.5
Noack volatility, 1h at 250 °C	% in weight	CEC L-40-93	<13

The above mentioned characteristics are typical values and should not be considered product specifications.