



MAKER CHAIN SAE 30 Y 40

Description

Repsol's Maker Chain SAE 30 & 40 lubricants are formulated from carefully selected bases which have been treated so as to significantly enhance their natural adherence.

General greasing oils specially suitable for lost lubrication applications (oil bottle, brush, etc.). Specially recommended for the lubrication of chainsaw chains.

Properties

- High viscosity index
- High slipperiness
- Good anti-corrosion protection

Quality levels, approvals and recommendations

• THYSSENKRUPP: 73* (40)

• DIN: 51501 L -AN (30, 40)

• ISO: 6743/1 - AN (30, 40)

*Formal approval

Technical specifications

	UNIT	METHOD	VALUE	
SAE Grade			30	40
Kinematic viscosity at 40 °C	cSt	ASTM D445	100	150
Kinematic viscosity at 100 °C	cSt	ASTM D445	11	14.5
Viscosity index		ASTM D2270	95	95
Flash point, open cup	°C	ASTM D92	210	220
Pour point	°C	ASTM D97	-15	-10
Corrosion Cu, 3hrs 100 °C		ASTM D130	1a	1a
Rust, method A		ASTM D665	Pass	Pass
Density at 15 °C	g/cm3	ASTM D4052		0.886

The above mentioned characteristics are typical values and should not be considered product specifications.