



# MAKER TURBO ARIES PLUS

## Description

Zinc-free lubricant formulated with hydrocracked bases, specially designed for lubrication of latest-generation gas and steam turbines without EP requirements. Characterized essentially by its exceptional resistance to oxidation, considerably extending its service life. The oil has been formulated with carefully selected GIII bases and antioxidant additives, corrosion and rust inhibitors and anti-foaming agents that confer excellent water separability properties, resistance to emulsion formation and anti-foam characteristics.

Lubricant suitable for gas turbines, steam turbines and turbochargers that work at high temperatures and require high performance to the lubricant.

## Properties

- Extraordinary resistance to ageing and sludge formation.
- High resistance to rust.
- Great water separation capacity.
- Excellent anti-foam properties.
- Very good air elimination.

## Quality levels, approvals and recommendations

- MAN: 10000494596-Rev.02.\* (46)
  - DIN: 51515, L-TGP (32, 46)
  - GEK: 46506E, 32568j, 120498, 107395A, 28143b (32)
  - HOWDEN & KKK (46)
  - ISO: 6743/4 HM, 11158 HM (32, 46)
  - ISO: 6743/6-CKB (32, 46)
  - SOLAR: ES 9-224 AA Class II (32, 46)
  - DIN: 51506 - VDL (32, 46)
  - GEK: 121608b (32)
  - GEK: 46506E, 32568j, 120498, 28143b (46)
  - ISO: 6743/3 - DAB, DAH (32, 46)
  - ISO: 6743/5 TGB/TSA (32, 46)
  - SIEMENS: TLV 901304 and TLV 901305 (Turbosets without Gearbox)\* (46)
- \*Formal approval

## Technical specifications

The above mentioned characteristics are typical values and should not be considered product specifications.