



## QUALIFIER BRAKE FLUID DOT 4

### Description

Synthetic brake fluid designed for hydraulic systems in motorcycles that operate in severe conditions where the recommended quality level is DOT 4 or DOT 3. Guarantees maximum efficiency and the highest stability in the functioning of the break pump.

### Properties

- High boiling point: above 260 °C
- Prevents foam formation.
- Highly resistant to oxidation.
- Compatible with joints and seals, thus preventing fluid loss risks.
- Contains inhibitors that prevent corrosion of the metal components of the circuit.

### Quality levels, approvals and recommendations

- Approved by the official INTA laboratory according to UNE 26-109-88
- ISO: 4925
- FMVSS: 116 DOT 4
- SAE: J 1703/J 1704

### Technical specifications

	UNIT	METHOD	VALUE
Appearance		Visual	Yellowish liquid
Water content	ppm		<2,000
Density at 20 °C	g/cm3	ASTM D1298	1.04
Viscosity at -40 °C	cP	SAE J1704	<1,500
Kinematic viscosity at 100 °C	cSt	ASTM D445	>1.5
Reflux boiling point	°C	SAE J1704	260
Wet boiling point	°C	SAE J1704	160
pH value		SAE J1704	9

The above mentioned characteristics are typical values and should not be considered product specifications.