



SAILOR GEAR GL-5 80W-90

Description

Multigrade lubricating oil designed for transmission systems of all those boats that require an API GL-5 quality level. Thanks to its EP additives, the transmission system is protected from wear caused by the high pressures it must withstand.

Exceeds the performance of automotive transmission oils in marine applications. Suitable for 2T or 4T gasoline inboard or outboard engine gears of all major marine manufacturers, e.g. Yamaha, Nissan, Suzuki, Honda, Tohatsu, Lehr. May not be suitable for some models.

Properties

- High capacity to withstand high loads and temperatures.
- Excellent anti-wear and anti-rust properties in marine environments.
- Extends the life of the transmission and minimizes noise and vibration.
- Good resistance to aging

Quality levels, approvals and recommendations

- API: GL-5 (80W-90)

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			80W-90
Density at 15 °C	g/cm ³	ASTM D4052	0.895
Viscosity at 100 °C	cSt	ASTM D445	13.8
Viscosity at 40 °C	cSt	ASTM D445	133
Viscosity at -26 °C	cP	ASTM D2983	<150,000
Viscosity index	-	ASTM D2270	100
Flash point, open cup	°C	ASTM D92	200
Pour point	°C	ASTM D97	-30

The above mentioned characteristics are typical values and should not be considered product specifications.